



Fix the bracket in camera setting place, and then set the camera in.
Installation is completed after adjusting the direction and tighten the screw.

UHD. 4K

- IP68
- Easy
- Ceiling
- Wall
- Outdoor
- IR 08

Resolution	2160P (EX-SDI UHD)
Lens	Fixed lens 3.6mm, 4mm, 6mm / V/F Lens 2.8~8mm, 2.8~12mm, 3.5~16mm
Sensor	1/2.5 inch SONY CMOS (IMX-274)
Effective Pixels	4074(H) X 3046(V) = 12.4M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	EX-SDI UHD
Min.Illumination	0 Lux at IR On (IR LED 08)
White Balance	Auto / Auto Ext / Preset / Manual
Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec)
Function	DNR / ACE / WDR / BLC / HLC / Privacy / Motion / RS-485 / Sharpness / Smart IR / Brightness
Day & Night	AUTO (Day <-> Night TIME Change) , COLOR , B/W, EXTERN
Language	ENG, CHN, CHN(S), JPN, KOR
Temperature/Humidity	Operating (-10°C~+50°C / 30%~80% RH) / Storage (-20°C~+60°C / 20%~90% RH)
Power	DC12V [AC24V / DC12V DualPower (option)]
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : UHD 100M)

