


i5B63-RW-28

NDAA/TAA
Compliant product




*MAGIC IP H.265 ONVIF

- 5MP (2592x1944), Dual Stream
- Video Encoding H265/ H264
- 2.8mm Fixed lens
- Hi-power LED 2pcs (IR Range 20M)
- 0.01 Lux (color), WDR, 3D DNR, AWB
- 2way Audio(G711U/G711A coding), Alarm, Sensor
- IE6.0 and Above Browser/ P2P Cloud Service
- Built in SD card slot
- Anti-reflection guide window
- IP67, Compact IR bullet, 3-Axis bracket

SPECIFICATIONS

Image Sensor	1/2.8" SONY CMOS	
Resolution	2592(H) x 1944(V), 5MP	
Lens	2.8mm (F2.0) Fixed lens	
LED	Hi-power 2pcs (IR Range 20M)	
Video Compression	H.265 / H.264	
Video Bit rate	CBR / VAR	
Frame Rate	Main Stream	2592*1944, 2688*1520, 2560*1440, 2048*1520, 2304*1296, 1080P/720P@30Fps
	Sub Stream	D1/ VGA/ 640*360/ CIF@30fps
Shutter speed	Auto / Manual	
Day & Night	Automatic, External control, Manual, Timing	
Function	3D DNR/ WDR (120dB) / BLC/ Privacy Mask, Flip mode, Saturation, Brightness, Contrast, Hue, Sharpness adjustable, AWB, Anti-face over-exposure , Defog	
Network	IE6.0 , Safari, Chrome, FireFox, Opera, Edge Browser	
Protocol	HTTP / RTSP / DHCP / NTP / ONVIF, optional GB28181, RTMP	
System Compatibility	ONVIF T v17.06 (TBD)	
Interface	RJ45	
SD Storage	max. 128GB	
Audio in/out	Support, Codec G711U/G711A	
Alarm / Sensor / PoE	Support	
Power Supply	DC12V	
Temperature/Humidity	Operating (-10~ +50°C / 30~80% RH)	


DIMENSIONS (mm)




INSTALLATION

- Place the bracket base at the pre-drilled installation position and route the power/network cable to the connecting place.
- Fix the bracket base by using 3 mounting screws
- Attach the camera unit and control the bracket nut.
- Adjust the camera's viewing angle (Pan, Tilt)
- Tighten screws with L-wrench to fix the camera.

[Wall]



[Ceiling]



Pan&Tilt Adjustment

