


LOCK & UNLOCK
Zoom & Focus (Varifocal)
It is not possible to adjust Zoom Focus after tightening the screw with using the Phillips screwdriver but, it is possible after removing the screw.

UHD. 4K


Anti-reflection | Light | Easy | Ceiling | Wall | indoor | IR 06

Resolution	2160P (EX-SDI UHD)
Lens	Fixed lens 3.6mm, 4mm, 6mm / V/F Lens 2.8~8mm, 2.8~12mm, 3.5~16mm
Sensor	1/2.5 inch SONY CMOS (IMX-274)
Effective Pixels	4074(H) X 3046(V) = 12.4M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	EX-SDI UHD
Min.Illumination	0 Lux at IR On (IR LED 06)
White Balance	Auto / Auto Ext / Preset / Manual
Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec)
Function	DNR / ACE / WDR / BLC / HLC / Privacy / Motion / RS-485 / Sharpness / Smart IR / Brightness
Day & Night	AUTO (Day <-> Night TIME Change) , COLOR , B/W, EXTERN
Language	ENG, CHN, CHN(S), JPN, KOR
Temperature/Humidity	Operating (-10°C~+50°C / 30%~80% RH) / Storage (-20°C~+60°C / 20%~90% RH)
Power	DC12V [AC24V / DC12V DualPower (option)]
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : UHD 100M)


Dome glass Guide




There are 2 locations of dome glass Guide in IR cover. You must close the cover to suit deco direction of dome glass to Guide.



close the cover



Right Assembly



Wrong Assembly

If the combination of the hemisphere is wrong, the diffuse reflection may occur. Please check the combination direction of Hemisphere if the diffuse reflection occurs.